



T650 Thermal Platform Ordering Information

T650

Size _____

1 6.75" X 6.75" (17.15 cm X 17.15 cm)
 2 11" X 11" (27.94 cm X 27.94 cm)

Voltage _____

1 115 VAC 50/60 Hz (110 to 120 VAC)
 2 230 VAC 50/60 Hz (208 to 240 VAC)

Coolant _____

1 LN₂ 15-25 PSIG (+130° C to -99° C)
 2 LCO₂ 300 PSIG (+130° C to -65° C)
 3 LCO₂ 900 PSIG (+130° C to -65° C)

PM6 Controller _____

B PM6 — Ramp & soak, 232/485 serial comms, FM approved limit/alarms†, 2nd device sensor, 7-segment LED display
 C PM6 — Ramp & soak, 232/485 Standard bus and Ethernet/IP—Modbus TCP serial comms*, 7-segment LED display
 D PM6 — same as B above, and add Bluetooth/EZ-LINK, SMOOTH-TOUCH™ keypad and high resolution LCD display
 E PM6 — same as C above, and add Bluetooth/EZLINK, SMOOTH-TOUCH™ keypad and high resolution LCD display
 †Option A without FM approved limit/alarm controller is no longer available. Order PM6 controller option B
 *Ethernet option replaces 2nd user device sensor and FM approved integrated limit/alarm controller

Country

- A Continental Europe (Austria, Germany, Netherlands, Spain, Sweden, etc.)
- C Australia/New Zealand
- D United Kingdom/Ireland
- E Denmark
- F France/Belgium
- G India/South Africa
- H Israel
- I Italy
- J Japan
- K USA (North America)
- L Switzerland
- O Russia
- X China
- T Argentina
- Z Stripped Leads (no plug on power cord)

Example: T650-113AK

T650 Thermal Platform System, 6.75" X 6.75", 115 VAC 50/60 Hz, LCO₂ 900 PSIG, Premium PM6 Temperature Controller and USA (North America) plug and power cord

Environmental Stress Systems, Inc. 21089 Longeway Road, Sonoma, CA 95370

Tel: +1.209.588.1993 Fax: +1.209.588.1997 Email: ess@essproducts.com Web: www.essproducts.com